

9112 Series

LED EXIT Light



General Description

9112 series of LED EXIT lights are wall mounted with option for wall flush mounting, making it suitable for final exit and also where exit signs are required directly above exit doors. Power consumption is low at only 3.5 watts, with the sleek decorative finish of Dynamic Pro.

This range has self contained models with manual or auto test options, and has battery option of 1 hr or 3 hrs standby time. The DALI models come with 3 hrs of battery stand by time.

The batteries are fully sealed, maintenance free, and safety tested as per EN standards. This luminaire has TUV approval, and has RoHS (Restriction of Hazardous Substances) compliance.

All models of this series luminaires will maintain the same lux output during the entire emergency mode operation as specified (only the battery being used to power the lamp and fitting controls). This is achieved as our luminaires are working with "constant current" technology. The same current output is maintained even if the battery voltage goes down. The luminaire lamp current is totally cut off when the battery voltage falls below a certain pre-determined voltage. Leaving enough charge to power the control module

AUTO Test

Auto-Test Option provides automatic testing of light fitting when used without DALI central monitoring option, and provides continuous monitoring of the unit and indicates service alert using dual-color LED lamp


The unit will automatically initiate a Self-Test and Self-Diagnostics test as follows:

- Verifies battery disconnection, charger failure, lamp failure and transformer
- failure at every 5 seconds.
- One minute self-testing every month.
- 30 minutes self-testing on the 6th month of the year after installation.
- 90 minutes self-testing on the 12th month of the year after installation.
- Automatically indicates lamp, battery and charger status by dual-color
- LED lamp.
- Factory preset - does not need field adjustment.



Main Features

- Compact and decorative design.
- LED self contained luminaire with manual test, AUTO test and DALI monitoring options.
- Ni-MH battery.
- Wall surface mounting and flush mounting.
- Replaceable pictogram design, including with arrow and no arrow pictograms in package.
- High luminance model optional.
- Low operation cost via low power consumption.
- Maintained and non-maintained operation changeable.
- Material of luminaire compliant with the glow wire test at temperature of 850C.
- RoHS compliance.





Manual Test

Tests are initiated manually, and can be initiated by the following action:

Press test button once	30 seconds test
Press test button twice (within 2 seconds)	3 minutes test
Press test button 3 times (within 2 seconds)	30 minutes test
Press test button 4 times (within 2 seconds)	1 hour or 3 hours test

Service Alert code for Manual Testing:


One blink ON/pause (4 seconds)	Battery is not connected
Two blink ON/pause (4 seconds)	Battery is shorted or Battery voltage drops below than acceptable value
Three blink ON/pause (4 seconds)	Charger board circuit fault
Four blink ON/pause (4 seconds)	Transfer fault
Five blink ON/pause (4 seconds)	Emergency lamp fault

TECHNICAL SPECIFICATION

Rated Power Supply	220-240VAC 50/60Hz
Power consumption	Max. 4.7W
Charge time	24 hours
Discharge duration	1hour/3hours
Changeover voltage	144-187VAC
Test facility	Manual test and AUTO test, DALI interface available
Viewing distance	24m(EU standard)
Operation	Maintained and Non-maintained
Mounting	Wall mounting and Flush mounting
LED	SMD 2835, CCT 6000K, CRI>70
Luminance of white area on pictogram	Normal luminance 200cd/m2 high luminance 500cd/m2
Safe color of Pictogram	Pantone 336C or Pantone 348C optional
Degree of protection	IP20
Insulation Class	Class II
Housing material	ABS
Ambient temperature	0C...+40C
Certification	CE, CB, TUV



DIMENSIONS (mm)



PICTOGRAM PACK



Arrow right 1pc



Without Arrow 1pc

**MODEL LIST**

Part number	Alternative part number	Test type	Discharge Duration	Battery	Power Consumption	LED
9112-1MH	ESA12/1H/MT/MH	Manual	1H	Ni-Mh 3.6V 0.6Ah	3.5W Max	SMD 2835 6000K 14LED
9112-3MH	ESA12/3H/MT/MH	Manual	3H	Ni-Mh 3.6V 0.9Ah	3.5W Max	SMD 2835 6000K 14LED
9112-1AH	ESA12/1H/AT/MH	AUTO	1H	Ni-Mh 3.6V 0.6Ah	3.5W Max	SMD 2835 6000K 14LED
9112-3AH	ESA12/3H/AT/MH	AUTO	3H	Ni-Mh 3.6V 0.9Ah	3.5W Max	SMD 2835 6000K 14LED
9112-3DH	ESA12/3H/DA/MH	DALI	3H	Ni-Mh 3.6V 2Ah	3.5W Max	SMD 2835 6000K 14LED

ORDER GUIDE

X-Y-Z ARE THE THREE ALPHABETS AFTER THE SERIES NUMBER OF THE MODEL

X		Y		Z	
Battery stand-by Duration		Type of test		Battery Type	
1	For 1 Hr	M	Manual testing	L	Lithium Iron Phosphate
3	For 3 Hrs	A	Auto Testing	C	Nickle cadmium
		D	DALI	H	Nickel metal Hydride